

Pin assignment

Pin assignment number: 193

Index:

26.05.2011

Connector name: 26-pol.CONTACT Pin-count: 26

Page: 1/1

Pin	Designation	Description	Level	Driver NC	Color
1	O_D0	Data output			white
2	O_D1	Data output			brown
3	O_D2	Data output			green
4	O_D3	Data output			yellow
5	O_D4	Data output			gray
6	O_D5	Data output			pink
7	O_D6	Data output			blue
8	O_D7	Data output			red
9	O_D8	Data output			black
10	O_D9	Data output			violet
11	O_D10	Data output			gray/pink
12	O_D11	Data output			red/blue
13	O_D12	Data output			withe/green
14	O_D13	Data output			brown/green
15	O_D14	Data output			withe/yellow
16	O_D15	Data output			yellow/brown
17	O_D16	Data output			withe/gray
18	O_D17	Data output			gray/brown
19	O_D18	Data output			withe/pink
20	Preset1_IN	Preset value 1	Supply Voltage	0	pink/brown
21	Direction IN	Change of counting direction	Supply Voltage	0	withe/blue
22	Ser.Program+_IN/OUT	Ser. programming interface RS485	RS 485	RS 485	brown/blue
23	Ser.Program-_IN/OUT	Ser. programming interface RS485	RS 485	RS 485	withe/red
24	Supply Voltage IN	Supply voltage	11-27V		brown/red
25	Ground IN	Ground	0V		withe/black
26	I_Latch	High=Latch	Supply Voltage	0	brown/black

WARNING !!

'De-energize the system before carrying out wiring work or opening and closing electrical connections !!!

Short-circuits, voltage peaks, etc. can cause operating failures and uncontrolled operating states, as well as serious personal injuries and damage to property.

Verdrahtungsarbeiten, Öffnen und Schließen von elektrischen Verbindungen nur im spannungslosen Zustand durchführen !!! Kurzschlüsse, Spannungsspitzen etc. können zur Fehlfunktion und unkontrollierten Zuständen der Anlage bzw. zu erheblichen Personen- und Sachschäden führen.